

Straw spreader - Sawdust spreader
for beddings, cubicles and feeders



bicieffe

Revolving unwinders for round bales with conveyor and straw-thrasher for beddings, cubicles and unloading in feeder

SBi SBi/i HYBRI



The SBi/i Hybrid is equipped with catenary of unrolling with sleepers which allow the use of very chopped products and, thanks to the independent motor on the conveyor and to the "short-straw kit", the parallelepipedal bales can be used.

SBi/SBi/i	Working width	Length unwinder	Length conveyor	Max height with bale on charge	Min. Power of the tractor	Width inner compartment
1480	1850	3400	1500/5500	2900	35 hp 25 kw	1480

Data here-shown are approximate and may change without notice

The SBi 1480 unwinders can hold a round bale of 120 cm base and any diameter.

Twines or wires that wrap the bales are easily eliminated by the operator after loading. You can also put the fork loading.

Machines are equipped with dual circuit hydraulic gear-case and are adjustable to work on both sides, with a rotation up to 270°. The conveyors have fixed or retractable lengths between 1.5 m and 5 m.

With the "cubicle kit" and the inversion of rotation of the straw-thrasher, the distribution of the product in the cubicle is ensured with a minimal amount of dust, produced only by a slight mechanical working in the absence of shredding and displacement of air masses. An hydraulic bulkhead perfects the jet, positioning it at the centre of the pillow or in the boxes with a depth of 2 to 6 m.

Without using the straw-thrasher you can get the unloading directly in the feeder leaving the forage (dry or half-dry) intact. A single machine can carry out three different tasks.

The straw-thrasher with four rows of springs ensure a jet of product up to 11 m of distance by the extremity of the conveyor.

The "short-straw kit" allows to move a bale behind the unrolling chains in the presence of particularly loose, damaged or deformed materials or of cornstalks.





The SBOi Bicieffe feeder-distributors can hold a bale of any size in the model 1480 and two bales (max 70x120) in the model 1780. Changing the speed of unrolling, both round bales and cornstalks can be used (they do not work with round bales of hay).

The straw-thrower with four rows of springs ensures a jet of product up to 11 m of distance by the extremity of the conveyor.

With the "cubicle kit" and the inversion of rotation of the straw-thrower, the distribution of the product in the cubicle is ensured with a minimal amount of dust, produced only by a slight mechanical working in the absence of shredding and displacement of air masses. An hydraulic bulkhead perfects the jet, positioning it at the centre of the pillow or in the boxes with a depth of 2 to 6 m.

Revolving feeder-distributor for parallelepipedal and round bales with conveyor and straw-thrower for beddings and cubicles

SBOi

Equipped with dual circuit hydraulic gear-case and adjustable to work on both sides, with a rotation up to 270°. The conveyors have fixed or retractable lengths between 1.5 m and 5 m.

SBOi	Working width	Length feeder-distributor	Length conveyor	Max height with bale on charge of 120		Min. Power of the tractor	Width inner compartment	N° of parallelepipedal bales
				Mobile support surface				
				Down	Up			
1480	1850	3400	1500/5500	2600	3600	35 hp 25 kw	1480	n°1 qualsiasi misura
1780	1850	3400	1500/5500	2600	3600	35 hp 25 kw	1780	n°2 max 70x120

Data here-shown are approximate and may change without notice

SPAND



The sawdust spreaders series SPAND Bicieffe 36 distribute optimally and uniformly the various types of sawdust, the wet separated, the chopped straw. The distribution is performed with a turbine that works without admission of air in order to contain the dust emission to a widely acceptable level.

These versions are worn with a three-point linkage at the tractor. The "pivoting wheels kit" is necessary to compensate for small tractors or in the presence of precarious gratings. The hydraulic gear-case replaces the direct attacks on the tractor when the control units of these are not enough, or in the presence of wet separated. In such a case the "shaker kit for separated" is inserted, so that it eliminates the formation of cavities. On request the large capacity of the container can be reduced in height to supply needs of passage.

Sawdust spreader, wood shavings, separated (dry and wet), rice husk and chopped straw mixed with calcium carbonate or lime and water

The SPAND Bicieffe 31 versions are self-loading models adaptable to any type of front or telescopic loader. With the same medium it is possible to discharge the material in cubicles, in a simple and easy way, using the auxiliary hydraulics distributors of the means in which they are engaged.



	Capacity	Max height with pivoting wheels	Width	Length without pivoting wheels	Weight empty base machine	Hydraulics couplings system	Power of tractor
SPAND 36	3,6 m ³	2450 (other measures on request)	1900	1550	630	200 bar 25 l/min (minimum)	From 35 hp 25kw until 90 hp 66kw Depending on the version and the used product

	Capacity	Height	Width	Length	Empty Weight	Hydraulic Supply	Carrying capacity of telescopic or front loader
SPAND 31	3,1 m ³	2000 (other measures on request)	1950	1550	700	200 bar 25 l/min (minimum)	1800 kg (minimum)

I dati riportati sono indicativi e soggetti a variazioni senza preavviso

Data here-shown are approximate and may change without notice



SBi

Revolving unwinders for round bales for unloading in feeder



The unwinders series SBI Bicieffe for feeder can hold a bale of 120 of hay, straw or half-dry. They can be supplied with different chains depending on the used product. In the roundup version, cheaper, using a double-acting hydraulic tractor with a two levers distributor on the machine, this allows the orientation and unrolling. They can be equipped with an independent unit and a loading fork. We also produce versions worn with a lift or a telescopic or front loader attachment, so as electric and fixed versions.

	Working width	Length unwinder	Max height with bale on charge	Min. Power of the tractor	Width inner compartment
SBi 1480	1850	3400	2900	35 hp 25 kw	1480

Data here-shown are approximate and may change without notice



VIA CANAVERE, 11 - 12038 - SAVIGLIANO - CN - ITALY
 TEL. +39.0172.71.50.14 r.a. - FAX +39.0172.71.59.66
 E-MAIL: info@bravosrl.it - INTERNET: www.bravosrl.it

